



UNIVERGE Desktop Digital Terminals

Fulfilling the promise of UNIVERGE®360

At a Glance

- Scalability and customization through modularity
- A full range of models and optional interfaces and modules
- Programmable line keys for immediate line/feature access or speed dialling
- Full duplex speaker (DT330)

UNIVERGE Desktop Digital Terminals offer features and benefits that brilliantly capture the essence of form and function while providing businesses the means to seamlessly communicate with their customers. These intelligent terminals help your business take service and performance to newer, more profitable heights.

Maximizing productivity

In today's intensely competitive business environment, smart companies know that it takes great customer service to get ahead.

Desktop Digital Terminals deliver exceptional value. With their user-friendly ergonomic design, a range of six models to choose from and a choice of interfaces and options, they provide users with access to the full power of UNIVERGE communication platforms.

Features		DT330	DT310
Display	Display size:	168x58 dot matrix B/W LCD Optional LCD backlit Optional 2nd display for DESI-less	6DE: 168x41 dot matrix B/W LCD, not backlit
	Characters x Lines:	Alphanumeric: 28x4 (6x12 font) DESI-less: 28x4 (6x12 font)	6DE: 24x3
	Tiltable:	Yes	N/A
Keypad	Backlit keypad:	Yes	N/A
	Line keys:	12, 24, 32 DESI-less: 8 x 4 pages	2, 6
	Softkeys:	4, help, exit	4, help, exit (only on 6DE)
	Cursor keys:	Yes	only on 6DE
Built In Applications	Personal directory:	Yes	No
	System directory:	Yes	No
	Corporate directory:	Yes	No
	Call history:	Yes	No
Sound	Hands-free:	Full duplex	Yes
Optional Adapters	Recording Adapter:	Yes	N/A
	Analogue Port Adapter w/ringer:	Yes	N/A
	PSTN survivable adapter:	Yes	N/A
Other	Headset support	Yes	No
	Wall mountable capability	Yes	Yes
Characteristics	Dimension (wxdxh):	12D/24D: 179x258x112 mm 32D (24D+8LK): 205.8x258x112 mm DESI-less: 179x264x112 mm	2E: 179x225x112 mm 6DE: 179x225x112 mm
	Weight (approx. kgs.):	12D/24D: 1.2 kg 32D (24D+8LK): 1.3 kg DESI-less: 1.3 kg	2E: 1.0 kg 6DE: 1.1 kg
	AC adapter (option):	27V 750mA	27V 750mA
Standards	EMC:	The Desktop Digital Terminals carry a CE mark and comply with: EMC: EN55022 Emission EN55024 Immunity EN61000 Powering	
	RoHS:	All models comply with RoHS	
	Safety:	EN60950-1	
	UL/CSA:	FCC Part 15 Class B FCC Part 68	
	Transmission and signalling:	TBR8	
Environmentals	Operating conditions:	Temperature range: 0 to 40 °C, humidity; 10 to 90% RH (not condensing)	
	Storage:	Ambient temperature range: -20 to 60 °C, ambient humidity: 10 to 90 %RH	

UNIVERGE360 is NEC's approach to unifying business communications. It places people at the center of communications and delivers on an organization's needs by uniting infrastructure, communications and business.

